

ULTRA EFFICIENT MULTI LED

Top binned 7W Cree LED provides the greatest light output from a multi source LED light of its size.

ADVANCED OPTIC TECHNOLOGY

Each led is focused using a 10° optic that allows for the flood pattern to achieve full beam spread

HIGHEST QUALITY SINGLE LED

Industry leading Luminus Big Chip Technology allows the Single Source Cannon reach unheard of distances.

IRIS REFLECTOR TECHNOLOGY

Focusing the power of the single source LED, the advanced IRIS Reflector shoots out a long distance spot beam.

50.000 HOURS

CANNON LCO/





25 LIGHTS

Each Light Cannon is 25 lights in one with the help of snap-on polycarbonate covers that can alter the beam pattern and change the color of the Cannon.

Tackle any weather condition with the proper color cover or quickly change your spot cover to a flood cover for a wider beam when necessary.



VISIONXEUROPE.COM

VISION X EUROPE Svarvarvägen 14 132 38 Saltsjö-Boo, Sweden +46 8 747 24 80 | info@visionxeurope.com



SPECIFICATIONS

MULTI CREE LEDS

Model	CG2-CPM310	CG2-CPM710	CG2-CPM1810	CG2-CPM2410
Size	3.7" - 9.5 cm	4.7" - 12 cm	6.7" - 17 cm	8.7" - 22 cm
LED (CREE)	(3) 7 W	(7) 7 W	(18) 7 W	(24) 7 W
Raw Lumens	2.250 lm	5.250 lm	13.500 lm	18.000 lm
Effective Lumens	1.575 lm	3.675 lm	9.450 lm	12.600 lm
Wattage	21 W	49 W	126 W	168 W
Amp Draw	1.75 A	4.08 A	10.5 A	14 A
IP Rating	IP68 / IP69K	IP68 / IP69K	IP68 / IP69K	IP68 / IP69K

CG2-CPM2410 430 m Range 18.000 Lumens 168 Watts OFM HI

CG2-CPZ810 1070 m Range 6.200 Lumens 100 Watts DEM HI

Model	CG2-CPZ110	CG2-CPZ610	CG2-CPZ810
Size	4.7" - 12 cm	6.7" - 17 cm	8.7" - 22 cm
LED (CREE)	(1) 40 W	(1) 70 W	(1) 100 W
Raw Lumens	3.000 lm	4.000 lm	6.200 lm
Effective Lumens	2.100 lm	2.800 lm	4.340 lm

CDEE

ANSION X

Raw Lumens	3.000 lm	4.000 lm	6.200 lm
Effective Lumens	2.100 lm	2.800 lm	4.340 lm
Wattage	40 W	70 W	100 W
Amp Draw	3.33 A	5.83 A	8.3 A
IP Rating	IP68 / IP69K	IP68 / IP69K	IP68 / IP69K



WEATHERPROOF CONNECTOR The Deutsch plug ensures the functionality of every Light Cannon even in the harshest conditions.

HEAT MANAGEMENT SYSTEM Advanced circuitry and aluminum heat sink design ensures maximum light output during sustained periods of use.

ADJUSTABLE AIMING SYSTEM Steel trunnion mount provides 45° of lighting adjustment secured by a robust locking system.

BUILT FOR HARSH CONDITIONS The IP68 / IP69K certified housing ensures a water tight seal even when completely submerged.

Ρ

